



**FORTRESS™**  
PERFORMANCE COATINGS



**HEAVY-DUTY**

**WATERPROOFING**

**WALL MEMBRANE**

**PU-80**



## DESCRIPTION

**FORTRESS Heavy-Duty Waterproofing Wall Membrane** is a one component, highly durable polyurethane modified membrane that is ideal for waterproofing any exterior walls. With its high UV resistance, flexibility and tough durability, **FORTRESS Heavy-Duty Waterproofing Wall Membrane** can be applied on bare walls without the need for primer. Highly recommended for application of firewalls, building walls and any exterior walls.

## COMPOSITION

Polyurethane Modified Emulsion  
Functional Fillers  
Titanium Dioxide

## FEATURES AND BENEFITS

- 100% Waterproof
- High Volume Solid
- High UV Resistance
- No Primer Needed
- No Topcoat Needed
- Fade Resistant
- Paintable



## APPLICATIONS

- Exterior Walls
- Concrete & Masonry Surfaces
- Bricks & Stucco
- Hollow Blocks
- Firewall & Partition Wall
- Drywall & Fiber Cement Boards
- Primed Wood & Metal Surfaces

## SURFACE PREPARATION

Surface must be clean, dry, stable and free from dirt, dust, oil, grease and other contaminants that will impede on the proper adhesion of the coating. New concrete structures need to be cured for at least 28 days prior to application.

All visible cracks should be sealed properly using **GreenSeal Waterproof Elastomeric Sealant**.

A minimum of three (3) coating applications of **FORTRESS** must be applied on the surface. Stir well before using. Curing time per coating application is 2 hours.



<b>PACKAGING</b>	4 liters, 16 liters
<b>COLOR</b>	Gray
<b>COVERAGE</b>	4 liters - 16.0 sq.m @ 0.25mm. wet film thickness / coat  16 liters - 64.0 sq.m @ 0.25mm. wet film thickness / coat
<b>DRYING TIME</b>	30 mins. @30 C - touch dry 1 hour @30 C - recoat 8 hours. @30 C - dry through



29-D GENERAL TIRONA STREET, CALOOCAN CITY, PHILIPPINES  
PHONE NO. (0917) 891 0539  
[www.campbridge.net](http://www.campbridge.net) • email: [campbridgepaint@gmail.com](mailto:campbridgepaint@gmail.com)